



Please find below a selection of our fast moving products, for full product list and further information please get in touch with us on +44 (0)1925 232662 or email us at mail@alliedexport.co.uk

► Cable Management

Cable Glands & Accessories



Brass Glands Kits

- 20-32mm kits include
 - 2 Glands, 2 Shrouds
 - 2 Tags and Locknuts
- 40+mm kits include 1 of each

Washers for Glands

To improve anti-vibration and IP Rating.
• Test certificates and certificates of conformity can be supplied if requested.



► BW Industrial Brass Cable Gland

2 part brass gland with knurled entry suitable for steel wired armoured cables (SWA). Provides mechanical cable retention & electrical continuity.

Standard: BS EN 50262

Ingress Protection: IP2X EN 60529 - Indoor use

Clamping - 2 part armour lock

Protection Material: Brass BS2874

Operating Temperature: -80°C to +300°C



Code	Size
BW20S	20mm Small
BW20	20mm
BW25	25mm
BW32	32mm
BW40	40mm
BW50	50mm
BW63	63mm
BW75	75mm

► CW Industrial Brass Cable Gland

3 part brass gland suitable for steel wired armoured cables (SWA). Provides an environmental seal on the outer sheath and also mechanical cable retention & electrical continuity.

Standard: BS EN 50262

Ingress Protection: IP66 – dust tight and protected against powerful water jets
Clamping – 2 part armour lock

Protection Material: Brass BS2874

Seal: TPE (Thermoplastic Elastomeric)

Operating Temperature: -20°C to +80°C



NEW
SIZES

Code	Size
CW20S	20mm Small
CW20	20mm
CW25	25mm
CW32	32mm
CW40	40mm
CW50	50mm
CW63	63mm
CW75	75mm

► CXT Industrial Brass Cable Gland

2 part brass gland suitable for wire braid / wire braid armour cables (CY, SY type). Provides an environmental seal on the outer sheath and also mechanical cable retention & electrical continuity.

Standard: BS EN 50262

Ingress Protection: IP66 – dust tight and protected against powerful water jets
Clamping – unique integral of teased braids

Protection Material: Brass BS2874

Operating Temperature: -20°C to +80°C



Code	Size
CXT20S	20mm Small
CXT20	20mm
CXT25	25mm
CXT32	32mm
CXT40	40mm
CXT50	50mm

► E1W Industrial Brass Cable Gland

2 part brass gland suitable for steel wired armoured cables (SWA)
Providing environmental seal on both the Cable Inner & Outer Sheaths so can be used in more hazardous areas.

Also provides mechanical retention & electrical continuity.

Standard: BS EN 50262

Ingress Protection: IP66 – dust tight and protected against powerful water jets
Clamping – Detachable armoured Cone & outer clamping Ring

Protection Material: Brass BS2874

Operating Temperature: -20°C to +80°C



Code	Size
E1W20S	20mm Small
E1W20	20mm
E1W25	25mm
E1W32	32mm
E1W40	40mm
E1W50	50mm

► A2 Industrial Brass Cable Gland

2 part brass gland suitable for un-armoured cables
The outer seal grips the sheath of the cable to achieve a weatherproof seal.

Standard: BS EN 50262

Ingress Protection: IP65 – dust tight and protected against water jets

Clamping – outer displacement seal

Protection Material: Brass BS2874

Operating Temperature: -20°C to +80°C



Code	Size
A220S	20mm Small
A220	20mm
A225	25mm
A232	32mm
A240	40mm
A250	50mm

► Cable Management

Cable Glands & Accessories

► LSF Shroud Packs

To make your glands LSF without buying the whole kit.



Code	Size
SHR20	To fit BW20
SHR20S	To fit BW20S
SHR25	To fit BW25
SHR32	To fit BW32
SHR40	To fit BW40
SHR50	To fit BW50
SHR63	To fit BW63
SHR75	To fit BW75

► Washer Nylon

Usage: To improve IP ratings on brass glands

Standard: Mechanical Tension: ISO 527 1-2

Material: Ertalon 6 SA

Colour: Natural (White)



Code	Size
NW20	20mm
NW25	25mm

► Washer Fibre

Usage: To improve IP ratings on brass glands

Standard: Mechanical IEC 667 1-2-3

Material: Vulcanized fibre (Type PG)

Colour: Red



Code	Size
FW20	20mm
FW25	25mm
FW32	32mm
FW40	40mm
FW50	50mm
FW63	63mm

► Shakeproof Washer

Shakeproof Washer For Glands

Standard: DIN 6797

Finish: Zinc & Clear

Usage: To improve non-vibration

Code	Size
ISSPW4	M4
ISSPW5	M5
ISSPW6	M6
ISSPW8	M8

ISSPW10	M10
ISSPW12	M12
ISSPW16	M16
ISSPW20	M20 for Glands
ISSPW25	M25 for Glands



► TRS Glands Brass with Rubber Seal

Standard: BS4568 & BS31 where applicable

Material: Brass with rubber seal

Finish: Brass



Code	Size
TRS20	20mm
TRS25	25mm